



HY-TEN GABION SOLUTIONS
Dunstall Hill Trading Estate,
Gorsebrook Road, Wolverhampton, WV6 0PJ
Tel 01902 712200 Fax 01902 714096
e-mail sales@hy-tengabions.com
web www.hy-tengabions.com

Triple Life 5.0mm wire diameter

Gabions shall comply with the following specifications

MANUFACTURE	<p>Gabions shall be manufactured from a hard drawn steel wire formed into a bi-axial mesh grid by electrically welding the cross wires at every intersection.</p> <p>Gabions:-to be factory assembled with triple life C rings connecting side panels and diaphragms to the base panel.</p>
MESH SIZE	<p>Mesh openings shall be square of nominal dimension of 76.2mm on the grid.</p>
MESH WIRE	<p>Nominal wire diameter shall be 5.0mm to BS 1052</p>
CORROSION PROTECTION	<p>Wire shall be triple life (95% zinc 5% aluminium) coated.</p>
JOINTING	<p>Gabions shall be provided with lacing wire for site assembly. Lacing wire shall be of minimum wire diameter 2.2mm (all in accordance with the corrosion specified) for final jointing.</p>
ROCKFILL	<p>Gabion fill shall be a hard durable and non frost susceptible (rock or stone type) having a minimum dimension not less than the mesh opening and a maximum dimension of 200mm.</p>
CONSTRUCTION	<p>All rockfill shall be packed tightly to minimize voids and the rockfill on the exposed face of the gabion is to be hand packed.</p> <p>Internal windlass bracing ties 2 per 1sqm at 1/3rd points vertically and mid point horizontally on 1m deep units and at mid height at mid point horizontally on 0.5m deep units.</p> <p>Adjacent units to be jointed by continuous lacing on vertical and to the horizontal joints at front and rear of coursing joints.</p> <p>Units shall be filled such that the mesh lid bears onto the rock fill. The lid shall be wired down on all joints and across the diaphragms.</p>